

1500Vdc Containerized Energy Storage & Transformer Turnkey System

BCS2000K~2500K-C-HUD/T2 Series



Safe

- On-line insulation detection
- Adapt to extreme environment, such as high temperature, salt, and extreme cold etc.
- Real-time transformer condition monitoring



Smart

- Grid forming technology, providing extra inertial support.
- Millisecond-level power response, stable power grid operation.
- Multiple functions, including Black-Start and VSG etc.



Simple

- Integrated design of converter and transformer system, integrated system, Integrated data acquisition and optic fiber network.
- Wide DC voltage operation range, flexible configuration.
- Adapt to multiple scenarios, including power generation side, grid side and user side application, supporting multi-device parallel.



Technical Specification

Items	BCS2000K-C-HUD/T2	BCS2500K-C-HUD/T2
DC input		
Max. DC voltage	1500Vdc	
DC voltage range	1000-1500Vdc	
Max. DC current	1122A*2	1403A*2
Soft start	Yes	
AC output (On-grid)		
Rated AC output power	2000kW	2500kW
Max. AC output power	2200kVA	2750kVA
Rated grid-tied voltage	690Vac 3P3W+PE	
Grid voltage range	-15%~10% (settable)	
Grid frequency range	50/60Hz	
Max. output current	1841A	2301A
Power factor	>0.99 (at rated power)	
Adjustable power factor	1 (leading)~1 (lagging)	
THDi	<3% (at rated power)	
AC output (Off-grid)		
Rated AC output voltage	690Vac	
Output voltage accuracy	1%	
Max. output current	1841A	2301A
THDu	<3% (liner load)	
Rated output frequency	50/60Hz	
Overload capability	110% overload	
PCS efficiency		
Max. efficiency	99%*	
Transformer		
Rated power	2000kVA	2500kVA
Voltage transformation ratio	0.69/(6~33)kV (Can be customized)	
Isolation mode	oil-immersed transformer	
General data		
IP rating	IP65(PCS) IP54(Skid)	
Operation temperature	-35°C~60°C (>45°C derating)	
Relative humidity	0~100% (no-condensing)	
Cooling type	Intelligent air cooling	
Dimensions (W×H×D)	6058×2896×2438mm	
Weight	<13000kg	<14000kg
Altitude	2000m (>1000m derating)	
Display	LED	
Communication protocol	Modbus-RTU, Modbus-TCP, IEC61850, IEC104	
Communication interface	RS485, CAN, Ethernet	

- * This efficiency value was measured in a laboratory environment.
- * Specification indexes may be subject to changes without further notice

XIAMEN KEHUA DIGITAL ENERGY TECH CO.,LTD.

Add: Room 208 - 38, Hengye Building, No. 100 Xiangxing Road, Torch High-tech Zone (Xiang'an) Industrial Zone, Xiamen, China(361000)

Tel: +86-592-5160516

Fax: +86-592-5162166

Email: Intertrade@kehua.com

Web: www.kehua.com

